Product Name: PAINT SEALANT - QUART

Product identifier: 10-QT **Revision Date:** 05-27-2015

Replaces:



1. Identification

Product Name: PAINT SEALANT - QUART

Product identifier: 10-QT **Relevant identified uses of the** Paint

substance or mixture and uses

Chemical Manufacturer /

advised against:

Auto Wax - An ITW Company

Importer: Auto Magic®

1275 Round Table Drive

Dallas, TX 75247

Emergency telephone number: CHEMTREC: 1-800-424-9300

CANUTEC: 1-613-996-6666

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols:





GHS Classification: Carcinogenicity Category 1B

Flammable Liquid Category 3

GHS Signal Word: Danger

GHS Hazard Statements: Flammable liquid and vapour.

May cause cancer.

GHS Precautionary Statements:

Safety Precautions: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

Product Name: PAINT SEALANT - QUART

Product identifier: 10-QT **Revision Date:** 05-27-2015

Replaces:

Use personal protective equipment as required.

First Aid Measures: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use for extinction. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal: Dispose of contents/container in accordance with

local/regional/national/international regulation for hazardous wastes.

Hazards not otherwise

classified:

Storage:

No data available

3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
Hyrotreated Heavy Naphthe	68551-16-6	5 - 10
Distillates (Petroleum), Hydrotreated	64742-52-5	0.5 - 1.5
Heavy Naphtha		

the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret is required.

4. First-aid measures

Eye Contact: Flush eyes with plenty of water for at least 20 minutes retracting

eyelids often. Tilt the head to prevent chemical from transferring to

the uncontaminated eye. Get immediate medical attention.

Skin Contact: Wash with soap and water. Remove contaminated clothing and

launder. Get medical attention if irritation develops or persists.

Inhalation: Remove to fresh air. If breathing is difficult, have a trained

individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get

medical attention immediately

Ingestion: Do not induce vomiting and seek medical attention immediately.

Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS. If swallowed, have a trained medical professional induce vomiting immediately. Never give anything by

mouth to an unconscious person. Get medical attention

immediately.

Immediate medical attention and special treatment needed,:

No additional first aid information available

Product Name: PAINT SEALANT - QUART

Product identifier: 10-QT **Revision Date:** 05-27-2015

Replaces:

5. Fire-fighting measures

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water

spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire. Do not direct a water stream directly

into the hot burning liquid.

Unsuitable extinguishing media: No data available

Fire and/or Explosion Hazards: Vapors may be ignited by sparks, flames or other sources of ignition

if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition

and flash back.

Hazardous Combustion

Products:

Special protective equipment and precautions for fire-

fighters:

Carbon dioxide, Carbon monoxide, Formaldehyde, Silicon dioxide

Do not enter fire area without proper protection including selfcontained breathing apparatus and full protective equipment. Fight

fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.

Flammable component(s) of this material may be lighter than water

and burn while floating on the surface.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to

the spill.

Methods and material for containment and cleaning up:

No special spill clean-up considerations. Collect and discard in

regular trash.

7. Handling and storage

Precautions for safe handling: Harmful or irritating material. Avoid contacting and avoid breathing

the material. Use only in a well ventilated area.

Conditions for safe storage: Materials to Avoid/Chemical

Incompatibility::

Store in a cool dry place. Isolate from incompatible materials. Strong oxidizing agents Strong acids Strong alkalies Acidic

conditions Aluminum alloys

Product Name: PAINT SEALANT - QUART

Product identifier: 10-QT Revision Date: 05-27-2015

Replaces:

8. Exposure controls/personal protection

Limits:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL		
No data available					
Appropriate engineering	No exposure limits exist	for the constituents of this p	product. Use		
controls.:	local exhaust ventilation or other engineering controls to minimize				
	•	operator comfort. Engineer	9		
	must be designed to meet the OSHA chemical specific standard in				
	29 CFR 1910. Use process enclosures, local exhaust ventilation, or				
	other engineering controls to control airborne levels below				

Eye Protection: Wear chemically resistant safety glasses with side shields when

recommended exposure limits

handling this product. Do not wear contact lenses. Wear goggles

and a Face shield

Skin Protection: Wear protective gloves. Inspect gloves for chemical break-through

and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work Where use can result in skin contact, practice good personal hygiene. Use of

protective coveralls and long sleeves is recommended.

Respiratory Protection: Respiratory protection may be required to avoid overexposure

when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place

conditions warrant the use of a respirator.

Other Protective Equipment: Wear goggles and a Face shield Where use can result in skin

contact, practice good personal hygiene. Use of protective coveralls

and long sleeves is recommended.

9. Physical and chemical properties

Appearance (physical state): Liquid

Color: White/Neutral Odor: Hydrocarbon Odor threshold: No data available PH: No data available Melting Point/Freezing Point (°C): No data available

Initial Boiling Point and Boiling Range (°C): 100 Flash Point (°C): 43

Product Name: PAINT SEALANT - QUART

Product identifier: 10-QT **Revision Date:** 05-27-2015

Replaces:

Evaporation Rate:

Flammability (solid, gas):

Upper Flammable/Explosive Limit:

No data available

17.5 MMHG@20C/68F

Vapor Density:

No data available

Relative Density:

Solubility(ies): Insoluble

Partition coefficient: n-octanol/water:No data availableAuto-ignition Temperature (°C):No data availableDecomposition Temperature::No data availableViscosity:No data available

VOC (as packaged-less exempts and water) <10% or

10. Stability and reactivity

Reactivity: No data available

Chemical stability: Stable under normal conditions. **Conditions to avoid:** None known. Contamination.

Incompatible materials: Strong oxidizing agents Strong acids Strong alkalies Acidic

conditions Aluminum alloys

Hazardous decomposition

products:

Carbon dioxide Carbon monoxide Formaldehyde Silicon dioxide

11. Toxicological information

Likely routes of exposure (inhalation, ingestion, skin and eye contact):

Inhalation, Ingestion, Skin contact, Eye contact, Absorption

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation: Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and

headache.

Inhalation Toxicity: Harmful! Can cause systemic damage (see "Target Organs)

Skin Contact: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause

permanent damage.

Skin Absorption: No absorption hazard in normal industrial use.

Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently

injure eye tissue.

Ingestion Irritation: Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea,

vomiting and diarrhea.

Ingestion Toxicity: Harmful if swallowed. May cause systemic poisoning.

Product Name: PAINT SEALANT - QUART

Product identifier: 10-QT **Revision Date:** 05-27-2015

Replaces:

Long-Term (Chronic) Health Effects:

Carcinogenicity:None of the substances have been shown to cause cancer in long term animal

studies. Not a carcinogen according to NTP, IARC, or OSHA.

Reproductive andNo data available to indicate product or any components present at greater than

Developmental Toxicity: 0.1% may cause birth defects.

Mutagenicity:No data available to indicate product or any components present at greater than

0.1% is mutagenic or genotoxic.

Inhalation: Upon prolonged and/or repeated exposure, can cause moderate respiratory

irritation, dizziness, weakness, fatigue, nausea and headache. Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs) Upon prolonged or repeated contact, can cause moderate skin irritation, defatting,

and dermatitis. Not likely to cause permanent damage.

Skin Absorption: Upon prolonged or repeated exposure, no hazard in normal industrial use.

Component Toxicology Data

Skin Contact:

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50	
No data available				

Has the chemical been classified as a Carcinogen by NTP, IARC or OSHA.

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No data available			

12. Ecological information

Ecotoxicity (aquatic andThis material is not expected to be harmful to the ecology.

terrestrial, where available):

Persistence and degradability:No data availableMobility in soil:No data availableOther adverse effects (such asNo data available

hazardous to the ozone layer):

Ecological Toxicity Data

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available			

13. Disposal considerations

Description of waste residues: Spent or discarded material is a hazardous waste.

Waste treatment methods Dispose of by incineration following Federal, State, Local, or

(including packaging): Provincial regulations.

Waste Disposal Code(s): D001

Product Name: PAINT SEALANT - QUART

Product identifier: 10-QT **Revision Date:** 05-27-2015

Replaces:

14. Transport information

UN proper shipping name: Refer to bill of lading or container label for DOT or other

transportation hazard classification, if any.

15. Regulatory information

TSCA Status: All components in this product are on the TSCA Inventory.

Regulated Components:

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
No data available					

16. Other information, including date of preparation or last revision.

Revision Date: 05-27-2015

Revision Number: 4

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances