



Product Bulletin



CLEAR CUT™ COMPOUND

Product Description:

Medium duty, creamy machine cleaner formulated for use on factory applied and refinish clear coat paints. Synthetic micro abrasives quickly and safely remove new car finish blemishes, acid rain damage, water spots, light to moderate oxidation and 1200-1500 grit wet sand scratches. Leaves a clean, glossy surface ready for polishing. For hand or machine use. Safe for all types of paint finishes. CONTAINS NO WAX OR SILICONE. BODY SHOP SAFE. VOC COMPLIANT.

Product Details:

VOC Compliant
Body Shop Safe
NPE Free
Phosphate Free
pH: 9.6
Color: Light Blue
Fragrance: Floral

Packaging:

Pint: P-26-P
Gallon: P-26



Features & Benefits:

Removes Moderate Oxidation, Wet Sand Scratches, Cobwebs, Water Spots & More
Leaves a Smooth Surface Ready for Polishing
Safe for All Types of Paint Finishes
Body Shop Safe - Contains No Wax or Silicone

Application: *Shake well before using. Read label before use. See SDS for more information.*

D/A Polisher: Use a PRO® YU-7-C D/A Yellow Polish Pad. For more aggressive action, use a PRO® BU-7-C D/A Blue Compound Pad. Apply product to pad. Set dual action polisher to 4-5. Turn on polisher and buff with adequate pressure, spreading product evenly over surface. As product disappears, reduce pressure and polish to a glossy finish. Clean pad often to remove contaminants.

High Speed Buffer: Use a PRO® OV-85-C Orange Foam Compound Pad. Apply product to pad and spread evenly over small area of paint surface before buffing. Buff with adequate pressure at 1200-1800 rpm. As product disappears, reduce pressure and polish to a high gloss. Clean pad often to remove contaminants. Follow with the appropriate PRO® Buffing Pad and P-21 Swirl Eliminator™ & Polish. Finish with P-36 Cherry Finishing Wax™, P-63-Q Poly Gard™ or P-82 Carnauba Creme Wax™ to seal in depth and clarity with long term protection.

Helpful Tips:

Keep from freezing (32 °F/0 °C). Safety glasses and NIOSH approved dust mask are recommended while machine buffing this product. Do not apply in direct sunlight or onto a hot surface. For best results, wash vehicle exterior using PRO® C-60 Super Car Wash. Polish one section at a time.

Safety Data Sheet:

GHS Compliant. SDS can be found online at www.prowax.com.

BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com

