



Product Bulletin



TROUBLESHOOTER®

Product Description:

This sealer & color brightener is formulated to overcome the problem finishes such as metallics, blacks, reds and blues. Mild cleaners remove compound scratches, swirl marks, light oxidation and cobwebbing. It feeds the paint with the necessary oils to bring back depth and clarity, while carnauba and other waxes and polymers seal in the shine for long lasting beauty. For hand or machine use. VOC COMPLIANT.

Product Details:

VOC Compliant

NPE Free

Phosphate Free

pH: 8.5

Color: Light Orange

Fragrance: Floral

Packaging:

Gallon: P-33



Features & Benefits:

Revitalizes Faded Finishes by Restoring Lost Oils to the Paint

Mild Cleaners Remove Compound & Swirl Marks, Light Oxidation and Cobweb Scratches

Creamy Blend of Carnauba & Domestic Waxes Yield a Deep, Dark Shine

Formulated for Single Stage Black, Red & Metallic Paint Finishes

Application: *Shake well before using. Read label before use. See SDS for more information.*

Hand Use: Apply product to a clean microfiber wax applicator and spread evenly over small area of painted surface, rubbing well in a circular motion. Let dry to a haze (about 2 min.) and wipe off with a clean, microfiber towel. Polish by hand to a high gloss, turning towel while wiping down.

Orbital or D/A Polisher: Use a PRO® PB-12 Bonnet/YU-7-C Yellow Polish Pad. Apply product to bonnet/pad. Turn on polisher and buff with adequate pressure, spreading product evenly over surface. As product disappears, reduce pressure and polish to a high gloss finish. Clean pad often to remove contaminants.

High Speed Buffer: Use a PRO® RV-85-C Charcoal Foam Polish Pad or PRO® VA-80-C 50/50 Wool/Acrylic Light Compound Pad. Apply product to pad and spread evenly over small area of paint surface before buffing. Buff with adequate pressure at 1500-2300 rpm. As product disappears, reduce pressure and polish to a high gloss finish. Clean pad often to remove contaminants. For added protection, finish with PRO® P-36 Cherry Finishing Wax™, P-63-Q Poly Gard™ or P-82 Carnauba Creme Wax™.

Helpful Tips:

Keep from freezing (32 °F/0 °C). Do not apply in direct sunlight or onto a hot surface. For best results, wash vehicle exterior using PRO® C-60 Super Car Wash. Polish one section at a time.

Safety Data Sheet:

GHS Compliant. SDS can be found online at www.prowax.com.

BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY

(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com



INTERNATIONAL
CARWASH
ASSOCIATION®
GROWING. SMARTER. TOGETHER.